

Triple R BU100WG Filter System

Triple R offline / bypass oil filtration system

Article number(s): BU100WG / TR-19550

- Bypass filtration, installation on existing pressure.
- Installation on applications with a maximum pressure of 315 bar.
- Ideal for injection moulding machines, mobile hydraulics and aggregates.



PRODUCT DESCRIPTION


The BU100WG for purifying water glycol is connected to the system as a bypass, using the available pressure up to 315 bar. The system effectively filters all dirt particles, moisture, and oxidation products (resins) that are usually impossible to remove with standard filters. It can be combined with the WG100 and DWG100 filter elements.

TECHNICAL SPECIFICATIONS

Type system	Bypass, stationary / wall mounting	Liquid	Water glycol
For oil volumes up to	600L	Size	23 x 32
Weight	6,5	Filter housing material	Aluminum (treated)
Seal material	NBR	In / out	1/4 "x 3/8"
Max. inlet pressure	315	Minimum inlet pressure	10
Safety valve opens at	6	Number of filter elements	1
Max. viscosity	180 @ 40C	Flow	2
Country of origin	Japan	HScode	84212980
In the box	Package includes first (set of) element(s), mounting bracket and pressure gauge		

RECOMMENDED FILTER ELEMENTS & OPTIONS

OUR EUROPEAN PARTNERS



Element	Filtration / function	Article no.
Triple R WG100 Filter Element	10 µm absolute ß10 = 1000	Item number EL10012
Triple R DWG100 Filter Element	7 µm absolute ß7 = 1000	Item number EL10017

OPTIONS

No linked options found.

EUROPEAN DISTRIBUTION & TECHNICAL SUPPORT

Triple R Oil Cleaner | TRIS B.V.

European importer & distributor - Engineering - Assembly - Technical support
Topaasstraat 5, 7554 TJ Hengelo, The Netherlands | +31 74 242 8109
info@oilcleaner.eu | www.oilcleaner.eu

OUR EUROPEAN PARTNERS

